

SERVICE AT A GLANCE MAINTENANCE INTERVALS

FOR MACK MD SERIES; MODEL YEAR 2021, 2022, AND NEWER

CHASSIS	PERIOD	STANDARD INTERVAL	
Chassis Lubrication	Miles / KM / Time	15,000 / 24,000 / 12 months	
Electrical System Connectors (Check)	Time	Every 6 months	
Power Steering Fluid & Filter (Replace)	Miles / KM / Time	150,000 / 240,000 / 12 months	
Air Dryer Coalescing Cartridge (Replace)	Miles / KM / Time	150,000 / 240,000 / 12 months	

These maintenance intervals are general recommendations. Please refer to the appropriate maintenance and lubrication manual for your specific vehicle as the authoritative source for all details of a proper and complete inspection and maintenance plan for your vehicle. Recommended intervals by Miles, Km or Time, whichever occurs first.

ENGINE

Cummins engines service and support follow Cummins guidelines. The following information is provided for convenience. Customers should reference Cummins website for the authoritative information. In the event of any discrepancy between this document and Cummins, Cummins language prevails.

MAINTENANCE EVENT	EPA 2017 B6.7	EPA 2021 B6.7		
Oil and Filter Change	Up to 20k mi / 550 hr / 12 mo	Up to 30k mi / 1000 hr / 18 mo		
Fuel Filter Change	15k mi / 500 hr / 12 mo	60k mi / 2000 hr / 18 mo		
Crankcase Ventilations Filter Change	75k mi / 2,500 hr	Maintenance Free		
Valve Lash Adjust	150k mi / 5,000 hr	150k mi / 5,000 hr		
DPF Clean	200k mi / 6,500 hr	200k mi / 6,500 hr		
DEF Filter Change	200k mi / 6,500 hr	200k mi / 6,500 hr		

TRANSMISSION

Allison transmissions service and support follow Allison guidelines. The following information is provided for convenience. Customers should reference Allison Transmission website for the authoritative information. In the event of any discrepancy between this document and Allison, Allison language prevails.

Allison 2500HS; Allison 2500RDS		DUTY CYCLE	TES 295/468 Fluid	TES 389 Fluid
Fluid		General*	150k mi / 4,000 hr / 48 mo	50k mi / 2,000 hr / 24 mo
		Severe**	75k mi / 3,000 hr / 36 mo	12k mi / 500 hr / 6 mo
Filters	Spin-On Control Main Filter	General*	50k mi / 2,000 hr / 24 mo	50k mi / 2,000 hr / 24 mo
		Severe**	50k mi / 2,000 hr / 24 mo	12k mi / 500 hr / 6 mo
	Internal Filter	All	Overhaul	Overhaul

^{*}General Vocation: All vocations not classified as severe

^{**}Severe Vocation: On/off highway, refuse, city transit, shuttle transit